



SAFETY DATA SHEET

Revision Date 22-Jul-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name 97BR HIGH TACK SUPER ADHESIVE SEALANT 1.75 FL.OZ

Other means of identification

Product Code 80060

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA

Distributor

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex
(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|------------|
| Serious eye damage/eye irritation | Category 2 |
| Skin sensitization | Category 1 |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Flammable liquids | Category 2 |

Label elements

Emergency Overview

Danger

Causes serious eye irritation
May cause an allergic skin reaction
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor



Appearance Yellow

Physical state Liquid

Odor Ketone odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing should not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wear protective gloves/protective clothing/eye protection/face protection
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity 30.6669 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---------------------------------|------------|----------|--------------|
| ACETONE | 67-64-1 | 30 - 60 | * |
| ACRYLONITRILE-BUTADIENE POLYMER | 9003-18-3 | 10 - 30 | * |
| PHENOLIC RESIN | 25085-75-0 | 5 - 10 | * |
| METHYL ETHYL KETONE (BUTANONE) | 78-93-3 | 5 - 10 | * |
| N-HEXANE | 110-54-3 | 3 - 7 | * |
| TALC | 14807-96-6 | 1 - 5 | * |
| ETHYL ACETATE | 141-78-6 | 1 - 5 | * |
| 4,4 -ISOPROPYLIDENEDIPHENOL | 80-05-7 | 1 - 5 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

- General advice** Get medical advice/attention if you feel unwell.
- Eye contact** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Skin contact** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- Inhalation** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
- Ingestion** IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
- Self-protection of the first aider** Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO2), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Extremely flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Remove all sources of ignition.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store locked up.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|-------------------------------|--|--|
| ACETONE 67-64-1 | STEL: 750 ppm TWA: 500 ppm | TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm | IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³ |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | STEL: 300 ppm TWA: 200 ppm | TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³ | IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³ |

| | | | |
|---------------------------|--|--|--|
| N-HEXANE 110-54-3 | TWA: 50 ppm S* | TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³ | IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³ |
| TALC 14807-96-6 | TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction | (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit | IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust |
| ETHYL ACETATE 141-78-6 | TWA: 400 ppm | TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³ | IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³ |

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles).
- Skin and body protection** Wear protective gloves and protective clothing.
- Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance Yellow
Odor Ketone odor
Odor threshold No information available

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|--------------------------------|--------------------------|-------------------------|
| pH | No information available | |
| Melting point / freezing point | No information available | |
| Boiling point / boiling range | | |
| Flash point | < -18 °C / < 0 °F | |
| Evaporation rate | > 1 | Butyl acetate = 1 |
| Flammability (solid, gas) | No information available | |
| Flammability Limit in Air | | |
| Upper flammability limit: | 13.0% | |
| Lower flammability limit: | 1.0% | |
| Vapor pressure | 400 mm Hg | |
| Vapor density | >1 | Air = 1 |
| Relative density | 0.91 | |
| Water solubility | Partially soluble | |
| Solubility in other solvents | No information available | |
| Partition coefficient | No information available | |

| | |
|----------------------------------|--------------------------|
| Autoignition temperature | No information available |
| Decomposition temperature | No information available |
| Kinematic viscosity | No information available |
| Dynamic viscosity | No information available |
| Explosive properties | No information available |
| Oxidizing properties | No information available |

Other Information

| | |
|-------------------------|--------------------------|
| Softening point | No information available |
| Molecular weight | No information available |
| VOC Content (%) | 18.8% |
| Density | No information available |
| Bulk density | No information available |

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|---------------------|---|
| Inhalation | May cause irritation of respiratory tract. May cause drowsiness or dizziness. |
| Eye contact | Contact with eyes may cause irritation. May cause redness and tearing of the eyes. |
| Skin contact | May cause skin irritation and/or dermatitis. May cause sensitization by skin contact. |
| Ingestion | Ingestion may cause irritation to mucous membranes. |

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|--|--|---------------------------------------|
| ACETONE 67-64-1 | = 5800 mg/kg (Rat) | - | = 50100 mg/m ³ (Rat) 8 h |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | = 2483 mg/kg (Rat) = 2737 mg/kg (Rat) | = 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit) | = 11700 ppm (Rat) 4 h |
| N-HEXANE 110-54-3 | = 25 g/kg (Rat) | = 3000 mg/kg (Rabbit) | = 48000 ppm (Rat) 4 h |
| ETHYL ACETATE 141-78-6 | = 5620 mg/kg (Rat) | > 18000 mg/kg (Rabbit) > 20 mL/kg (Rabbit) | - |
| 4,4 -ISOPROPYLIDENEDIPHENOL 80-05-7 | = 3300 mg/kg (Rat) | = 3 mL/kg (Rabbit) | > 0.17 mg/L (Rat) 6 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|--------------------|-------|---------|-----|------|
| TALC 14807-96-6 | - | Group 3 | - | - |

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

| | |
|--------------------------------------|-------------|
| ATEmix (oral) | 5067 mg/kg |
| ATEmix (dermal) | 14660 mg/kg |
| ATEmix (inhalation-dust/mist) | 156.3 mg/l |
| ATEmix (inhalation-vapor) | 72569 mg/l |

12. ECOLOGICAL INFORMATION

Ecotoxicity

30.2585 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|---|---|--|---|
| ACETONE 67-64-1 | - | 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50 | 10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50 |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | - | 3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through | 520: 48 h Daphnia magna mg/L EC50 5091: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static |
| N-HEXANE 110-54-3 | - | 2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through | 1000: 24 h Daphnia magna mg/L EC50 |
| TALC 14807-96-6 | - | 100: 96 h Brachydanio rerio g/L LC50 semi-static | - |
| ETHYL ACETATE 141-78-6 | 3300: 48 h Desmodesmus subspicatus mg/L EC50 | 352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through | 560: 48 h Daphnia magna mg/L EC50 Static |
| 4,4 -ISOPROPYLIDENEDIPHENOL 80-05-7 | 2.5: 96 h Pseudokirchneriella subcapitata mg/L EC50 | 3.6 - 5.4: 96 h Pimephales promelas mg/L LC50 flow-through 4: 96 h Oncorhynchus mykiss mg/L LC50 9.9: 96 h Brachydanio rerio mg/L LC50 static 4.0 - 5.5: 96 h Pimephales promelas mg/L LC50 static | 10.2: 48 h Daphnia magna mg/L EC50 3.9: 48 h Daphnia magna mg/L EC50 9.2 - 11.4: 48 h Daphnia magna mg/L EC50 Static |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

| Chemical Name | Partition coefficient |
|---------------|-----------------------|
|---------------|-----------------------|

| | |
|---|-------|
| ACETONE 67-64-1 | -0.24 |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | 0.29 |
| ETHYL ACETATE 141-78-6 | 0.6 |
| 4,4 -ISOPROPYLIDENEDIPHENOL 80-05-7 | 2.2 |

Other adverse effects
No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001, D035

| Chemical Name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|--|------|--|-----------------------------|------------------------|
| ACETONE 67-64-1 | - | Included in waste stream: F039 | - | U002 |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | U159 | Included in waste streams: F005, F039 | 200.0 mg/L regulatory level | U159 |
| ETHYL ACETATE 141-78-6 | - | Included in waste stream: F039 | - | U112 |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|---|-----------------------------------|
| ACETONE 67-64-1 | Ignitable |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | Toxic Ignitable |
| N-HEXANE 110-54-3 | Toxic Ignitable |
| ETHYL ACETATE 141-78-6 | Toxic Ignitable |

14. TRANSPORT INFORMATION

DOT

UN/ID no 1133
Proper shipping name: Adhesives, Limited Quantity (LQ)
Hazard Class 3
Packing Group II
Emergency Response Guide Number 128

IATA

UN/ID no ID 8000
Proper shipping name: Consumer commodity
Hazard Class 9
ERG Code 9L

IMDG

UN/ID no 1133
 Proper shipping name: Adhesives, Limited Quantity (LQ)
 Hazard Class 3
 Packing Group II
 EmS-No F-E, S-D

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Complies
 ENCS Not determined
 IECSC Complies
 KECL Complies
 PICCS Complies
 AICS Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|---------------------------------------|-------------------------------|
| N-HEXANE - 110-54-3 | 1.0 |
| 4,4 -ISOPROPYLIDENEDIPHENOL - 80-05-7 | 1.0 |
| Formaldehyde - 50-00-0 | 0.1 |

SARA 311/312 Hazard Categories

Acute health hazard No
 Chronic Health Hazard No
 Fire hazard No
 Sudden release of pressure hazard No
 Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|--|--------------------------|----------------|--|
| ACETONE 67-64-1 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |
| N-HEXANE 110-54-3 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |

| | | | |
|---------------------------|---------|---|--|
| ETHYL ACETATE 141-78-6 | 5000 lb | - | RQ 5000 lb final RQ RQ 2270 kg final RQ |
|---------------------------|---------|---|--|

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name | California Proposition 65 |
|--------------------------------|--|
| Formaldehyde - 50-00-0 | Carcinogen |
| SILICA, QUARTZ - 14808-60-7 | Carcinogen |
| 4-VINYL CYCLOHEXENE - 100-40-3 | Carcinogen Female Reproductive Male Reproductive |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| ACETONE 67-64-1 | X | X | X |
| METHYL ETHYL KETONE (BUTANONE) 78-93-3 | X | X | X |
| N-HEXANE 110-54-3 | X | X | X |
| TALC 14807-96-6 | X | X | X |
| ETHYL ACETATE 141-78-6 | X | X | X |
| 4,4 -ISOPROPYLIDENEDIPHENOL 80-05-7 | X | X | X |
| Formaldehyde 50-00-0 | X | X | X |
| SILICA, QUARTZ 14808-60-7 | X | X | X |
| 4-VINYL CYCLOHEXENE 100-40-3 | X | X | X |
| PROPIONIC ACID ... % 79-09-4 | X | X | X |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

| | | | | |
|--------------------|-------------------------|-----------------------|---------------------------|------------------------------|
| <u>NFPA</u> | Health hazards 2 | Flammability 3 | Instability 0 | - |
| <u>HMIS</u> | Health hazards 2 | Flammability 3 | Physical hazards 0 | Personal protection B |

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 22-Jul-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet